



COMPRESSOR UNIT EKOM

TOWER

ideal for central distribution

Compressor unit **TOWER** with dryer **MONZUN** serves as the source of dry, clean, oil-free compressed air for the driving of pneumatic appliances and equipment. The unit consists of oil-free double-cylinder compressor aggregates placed in a solid steely frame. There are situated also pressure air tanks with the pertinent pneumatic fittings in the frame. Adsorption dryer of air **MONZUN** is fixed to the side panel of the frame. Thanks to its efficiency and economy operation, the unit is suitable as the central source of compressed air for large dental laboratories, dental clinics, hospital departments requiring compressed air of the required quality, as well as in the other fields of health-care practice and everywhere this version meets the given requirements.



	4 x 2V T	6 x 2V T	9 x 2V T	12 x 2V T	15 x 2V T	
Nominal voltage	3 x 400/50	3 x 400/50	3 x 400/50	3 x 400/50	3 x 400/50	V/Hz
Output capacity of the compressor	480	720	1080	1440	1800	l.min ⁻¹
Operation pressure of the compressor	5 - 7	5 - 7	5 - 7	5 - 7	5 - 7	bar
Air tank capacity	220	330	330	330	330	lit.
Degree of air drying	atmospheric dew point -20 °C					°C
Noise level	73	74	75	76	83	dB(A)
Weight	360	450	540	655	745	kg
Dimensions (w x d x h)	2460 x 1740 x 550	2460 x 1740 x 550	2910 x 1740 x 550	3460 x 1740 x 550	3910 x 1850 x 550	mm



8 - 15



EKOM s.r.o.
Priemyselná 5031/18
921 01 Piešťany
Slovak republic

tel.: +421 33 7967205
fax: +421 33 7967223
e-mail: ekom@ekom.sk
<http://www.ekom.sk>

